

HYDRAULIC PISTON PUMP SERIES



3 HP
73 cm³
5.5 ltr./min.
210 bar



HP41 on trolley MA-HP41

Features

Experience top performance and ultimate safety with our H-class electric motor! This quality level guarantees maximum reliability, even under extreme conditions and high temperatures. Thanks to an automatic system, the pump is immediately stopped when electrical safety limits are exceeded. All parts in contact with the product are made of high-quality stainless steel, ensuring the best performance at all times.

Applications

Acrylic • Rustproofing • Bituminous Coatings • Elastomers Emulsions • Fixatives • Funds • Plasters • Water-based paints Fireproof Coatings • Waterproofing Coatings Impregnating Coatings • Encapsulants Coatings Self-leveling plaster • Premixed plaster Intumescent • Insulators • Lacquers • Primer • Plasters Epoxy resins • Fillers • Enamels • Ready-mix Plasters • Paints

SPRAYPACK



	Technical data			
	Motor Volt	230 V		
		50 Hz		
	Power	3 HP		
	Pump Capacity per Double Stroke	73 cm ³		
	Max. Delivery	6.5 ltr./min.		
	Max. Delivery with tip	5.5 ltr./min.		
	Stroke	80 mm		
	Max. spray tip size	1 gun	0,041"	
		2 guns	0,021"	
	Max. working pressure	210 bar (3046 PSI)		
	Max. hose length	100 mt		
	Max. suggested viscosity	1.500		
	Weight	96 kg		

HP41 SprayPack	MA-HP41-SET	

 SprayPack contains

 15 mtr. hose Ø 3/8"
 H-T2-3/8-15

 1,8 mtr. hose whip Ø 1/4"
 H-W-1/4-1,8

 Airless gun, 500 bar, 5 mm ball
 AG500L

 X-Type tip base - 7/8"
 MT-X-BASE-G

 X-Type reversible tip - 423
 MT-X-423

